



# Pipe & Cable Locating Metrotech Arrow



Savcor supply and service the full range of Metrotech Pipe, Cable, Sheath location, and Water leak detection locators.

Our service department can also arrange training on locator operations, and are fully qualified by Metrotech to carry out all warranty repairs, calibrations, and repairs.

Depending on your needs, Savcor can advise you on the most operate locator for needs, whether it is a reliable affordable unit, or a high tech machine for user that require optimum performance in demanding environments.

*Typical applications:*  
Pipe Locating, Cable Locating, Sonde Locating

### Features:

- Tough, weatherproof design ensures year round durability
- High sensitivity and narrow response reveal buried lines
- Frequency-modulated audio tone provides a maximum signal at the centre of the line
- Fingertip controls for ease of use
- One-handed operation allows freedom of movement
- 45° angle depth measurement
- Combination automatic and manual gain control
- Automatic battery test at start-up

### Standard Equipment:

ARROW™ Receiver, Transmitter, Conductive Attachment, Ground Rod, Operations Manual and Carrying Bag

Optional Extras

### ARROW Builders Kit

Description: Arrow Receiver, Transmitter, Conductive Attachment, Ground Rod, 4435 MetroClamp, Small Sonde 35kHz, Carrying Bag, and Operations Manual.

### ARROW Electricians Kit

Description: Arrow Receiver, Transmitter, Conductive Attachment, Ground Rod, 4435 MetroClamp, Live Power Connector, Carrying Bag, and Operations Manual.

### ARROW Plumbers Kit

Description: Arrow Receiver, Small Sonde 35kHz, Carrying Bag, and Operations Manual.



### Metrotech Arrow Standard Kit

#### Technical Data

Transmitter: Output frequency 35.4 kHz,  
Output power 0.5 watts (conductive mode),

Battery Size D cells,  
Operation Temperature -20°C to +50°C  
Weight 2.5kg.

Receiver:  
Power: 50Hz – 60Hz  
Radio: (RF) 12kHz – 24kHz  
Active: (A) 35.4kHz  
Battery life: 60 hours of intermittent use  
Operation temperature -20°C to +50°C  
Weight 2.2kg

Vic/Tas/SA 03 9993 7500	NSW 02 9663 2322	NZ 09 414 5080	QLD/NT 07 3890 8533	WA 08 9248 8999
----------------------------	---------------------	-------------------	------------------------	--------------------

All written data and statements herein are provided in good faith and believed to be reliable and appropriate at the time of drafting this document. However it is given without implied or express guarantee. Potential uses are urged to trial and /or conduct conformity test of the product to deem its suitable in application for a particular end use prior to purchase.